


L(168F-177F)



L(182F-190F)

L Series

1/2 Chain Reducer L Series

SPECIFICATION	168F-2-L/168F-2D-L	170F-L/170FD-L	177F-L/177FD-L	188F-L/188FD-L	190F-L/190FD-L
Engine type	4 stroke, single cylinder, air cooled				
Bore*stroke(mm)	68*54	70*55	77*58	88*64	90*66
Displacement(cc)	196	212	270	389	420
Compression ratio	8.5:1	9:1	8.2:1	8:1	8.8:1
Net power (kw/rpm)	4.3/1800	4.6/1800	6.3/1800	9/1800	10.5/1800
Net torque (n.m/rpm)	25/1400	26/1400	36/1300	53/1400	56/1400
Ignition system	Non-contact transistorized ignition (TCI)				
Starting system	Manual/Electric start				
Air cleaner	Semi-dry type				
Oil capacity (L)	0.6	0.6	1.1	1.1	1.1
Fuel tank capacity(L)	3.6	3.6	6	6.5	6.5
Fuel consumption (g/kw.h)	≤395	≤374	≤374	≤374	≤370
Reducer mode	L	L	L	L	L
Net weight (kg)	18/20	18/20	26/28	33/35	33/35
Carton dimensions <(L*W*H)mm>	415*380*380	415*380*380	485*450*495	510*485*525	510*485*525
QTY<20GP/40GP/40HQ>	504/1020/1190	504/1020/1190	240/480/620	192/384/480	192/384/480