

## X1 Series/B Series/LIFAN Series

SPECIFICATION	168F-2/168F-2D	170F/170FD	177F/177FD	188F/188FD	190F/190FD
Engine type	4 stroke, single cylinder, air cooled				
Bore*stroke(mm)	68*54	70*55	77*58	88*64	90*66
Displacement(cc)	196	212	270	389	420
Compression ratio	8.5:1	9:1	8.7:1	8:1	8.8:1
Net power (kw/rpm)	4.3/3600	4.6/3600	6.3/3600	9/3600	10.5/3600
Net torque (n.m/rpm)	12.5/2800	13/2800	18/2600	26.5/2800	28/2800
Ignition system	Non-contact transistorized ignition (TCI)				
Starting system	Manual/Electric start				
Air cleaner	Semi-dry type				
Oil capacity (L)	0.6	0.6	1.1	1.1	1.1
Fuel tank capacity(L)	3.6	3.6	6	6.5	6.5
Fuel consumption (g/kw.h)	≤395	≤374	≤374	≤374	≤370
Net weight (kg)	16/18	16/18	25/27	31/33	32/34
Carton dimensions <(L*W*H)mm>	415*380*405	415*380*405	485*450*495	485*450*515	485*450*515
QTY<20GP/40GP/40HQ>	510/1020/1190	510/1020/1190	248/496/620	248/496/620	248/496/620



LIFAN Series(X1)



B Series



LIFAN Series