



X1



X6

## Standard Generator Series

SPECIFICATION	2200/2200E	2500/2500E	3500/3500E	5500/5500E	10500
Engine model	168F-2/168F-2D	168F-2/168F-2D	168F-2/168F-2D	188F/188FD	180F
Engine type	4 stroke, single cylinder, air cooled				
Starting system	Manual/Electric start				
Bore* stroke(mm)	68*54	68*54	68*54	88*64	80*62
Displacement(cc)	196	196	196	390	390
Max.power<(50Hz/60Hz)kw>	1.7/2.2	2.2/2.7	2.7/3.5	4.5/5.5	5.4
Rated power<(50Hz/60Hz)kw>	1.5/2	2/2.5	2.5/3	4/5	5
Rated voltage (V)	110/120/220/240	110/120/220/240	110/120/220/240	110/120/220/240	110/120/220/240
DC output (V/A)	12/8.3	12/8.3	12/8.3	12/8.3	12/8.3
Fuel consumption (g/kw.h)	≤450	≤450	≤450	≤480	≤480
Continuous running time (h)	12	10	10	9.5	9.5
Fuel tank capacity(L)	15	15	15	25	25
Net weight (kg)	41/42	41/42	51/53	77/80	77/80
Noise <(7m)dB>	≤65	≤65	≤65	≤72	≤72
Carton dimensions <(L*W*H)mm>	645*490*480	645*490*480	645*490*480	735*565*590	735*565*590
QTY<20GP/40GP/40HQ>	160/336/420	160/336/420	160/336/420	122/254/254	122/254/254